

1.

Each row has 12 possible states: RGB, RBG, BGR, BRG, GBR, GRB, RGR, RBR, GRG, GBG, BRB, BGB.

Let $OPT(n,i)$ be the maximum number of colorings for an $n \times 3$ matrix whose top row is in state i , for i in $1 \dots 12$.

The base case is $OPT(1,i)=1$ for all i .

The update rule: for each state of the top row, it is compatible with only certain states of the row below, which we can precompute. e.g. RGR is compatible with BRB but not BGB. Then let $OPT(n, i) = \sum_{j=1}^{12} OPT(n-1, j) * [\text{indicator that is 1 if state is compatible with state } j]$

Final output: sum of $OPT(N,j)$ for all j from 1 to 12. (summing up over all possible states of the top row)

Runtime: $O(N)$

Input: height of the matrix N

Output: number of ways to color the matrix

```
states=[\doBlank{rgb, rgb, bgr, brg, gbr, grb, rgr, rbr, grg, gb,
brb, bgb}] (5 pts)
# initialize a 2D OPT matrix of size N*|states| with all entries to
be zero
OPT[N, |states|] = 0
# base case
For s = 1 to |states|
    OPT[\doBlank{1, s}] = \doBlank{1} (2 pts)
EndFor
# dp update
For i = 2 to N
    For s1 = 1 to |states|
        For s2 = 1 to |states|
            state1 = states[s1]
            state2 = states[s2]
            If \doBlank{state1[1]!=state2[1] & state1[2]!=state2[2]
& state1[3]!=state2[3]} (5 pts)
                OPT[\doBlank{i, s1}]=\doBlank{OPT[i, s1] + OPT[i-1,
s2]} (5 pts)
            EndIF
        EndFor
    EndFor
EndFor
```

```
        EndFor
    EndFor
EndFor
Return \doBlank{sum(OPT[n, :])} (3 pts)
```

Note that `|states|` represents the length of the array `states`

2.

Given string $a = a_1 a_2 \dots a_n$ without spaces, we want to add spaces to break it into words $w_1 \dots w_k$ maximizing $\sum_i \text{score}(w_i)$.

Sol 1 $O(n^3)$ solution that should get full credit, though not optimal.

Let $\text{OPT}(i, j) = \text{maximum score for substring } a_i \dots a_j$.

$$\text{Notice } \text{OPT}(i, j) = \begin{cases} \text{score}(a_i \dots a_j) \\ \max_{t=i, i+1, \dots, j} \left[\text{OPT}(i, t) + \text{OPT}(t+1, j) \right] \end{cases}$$

with a base case of $\text{OPT}(i, i) = \text{score}(a_i) \quad \forall i = 1, \dots, n$. (single letters)

The DP matrix is $n \times n$, though we only use the half where $j \geq i$.

Each entry takes $O(n)$ time to compute for all values for t .

We fill in the DP matrix by increasing order of $j-i$.

Sol 2 $O(n^2)$ solution

Let $\text{OPT}(i) = \text{maximum score for substring } a_1 \dots a_i$.

$$\text{Notice } \text{OPT}(i) = \max \begin{cases} \text{score}(a_1 \dots a_i) \\ \max_{t=1 \dots i} \left[\text{OPT}(t) + \text{score}(a_{t+1} \dots a_i) \right] \end{cases}$$

with a base case of $\text{OPT}(1) = \text{score}(a_1)$.

The DP matrix is 1D and size n , and each entry takes $O(n)$ time to compute all values for t .

=====

3.

Initialize $Q(i, j, k) = 0$ if $i = 0$ or $j = 0$ or $k = 0$. This is because if at least one string is empty, there cannot be a common subsequence. The recurrence relation for dynamic programming is: \\

$Q(i, j, k) = Q(i - 1, j - 1, k - 1) + 1$ (if $a_i = b_j = c_k$)

$Q(i, j, k) = \max\{Q(i - 1, j, k), Q(i, j - 1, k), Q(i, j, k - 1)\}$

(if $a_i \neq b_j$ or $b_j \neq c_k$ or $c_k \neq a_i$)

Runtime for this algorithm is $O(N^3)$.